



CÓDIGO	Diâmetro do Chumbador e do Furo	Comprimento em Polegada	Comprimento em Milímetro	Carga Média Arrancamento no Concreto	Carga de Cisalhamento
				Kg	Kg
	Ø				
PB 14134	1/4"	1 3/4"	45	1.110	950
PB 14214	1/4"	2 1/4"	56	1.110	950
PB 14212	1/4"	2 1/2"	64	1.110	950
PB 14300	1/4"	3"	76	1.110	950
PB 14314	1/4"	3 1/4"	83	1.110	950
PB 14334	1/4"	3 3/4"	96	1.110	950
PB 56200	5/16"	2"	50	1.554	1.290
PB 56300	5/16"	3"	76	1.554	1.290
PB 56314	5/16"	3 1/4"	83	1.554	1.290
PB 56414	5/16"	4 1/4"	108	1.554	1.290
PB 38200	3/8"	2"	50	2.892	1.696
PB 38214	3/8"	2 1/4"	56	2.892	1.696
PB 38234	3/8"	2 3/4"	70	2.892	1.696
PB 38300	3/8"	3"	76	2.892	1.696
PB 38312	3/8"	3 1/2"	64	2.892	1.696
PB 38334	3/8"	3 3/4"	95	2.892	1.696
PB 38400	3/8"	4"	102	2.892	1.696
PB 38500	3/8"	5"	127	2.892	1.696
PB 12234	1/2"	2 3/4"	70	3.242	4.565
PB 12334	1/2"	3 3/4"	96	3.242	4.565
PB 12400	1/2"	4"	102	3.242	4.565
PB 12500	1/2"	5"	127	3.242	4.565
PB 12514	1/2"	5 1/4"	134	3.242	4.565
PB 12700	1/2"	7"	179	3.242	4.565
PB 58312	5/8"	3 1/2"	88	5.375	6.300
PB 58400	5/8"	4"	102	5.375	6.300
PB 58412	5/8"	4 1/2"	115	5.375	6.300
PB 58500	5/8"	5"	127	5.375	6.300
PB 58600	5/8"	6"	153	5.375	6.300
PB 58700	5/8"	7"	179	5.375	6.300
PB 58800	5/8"	8"	204	5.375	6.300
PB 34414	3/4"	4 1/4"	109	5.775	7.995
PB 34500	3/4"	5"	127	5.775	7.995
PB 34512	3/4"	5 1/2"	141	5.775	7.995
PB 34614	3/4"	6 1/4"	159	5.775	7.995
PB 34700	3/4"	7"	179	5.775	7.995
PB 34812	3/4"	8 1/2"	217	5.775	7.995

Obs: As cargas acima são limites máximos para fator de segurança, recomenda-se utilizar somente 25% das cargas.  
 Cargas apuradas em teste, efetuadas pelo Centro Tecnológico do Controle da Qualidade L.A. Fação Bauer Ltda.